

WAAS CH 60922 W13A	APP CRS 128°	Rwy Ldg TDZE 632 Apt Elev 661
--	------------------------	---

RNAV (GPS) RWY 13

GENERAL DOWNING - PEORIA INTL (PIA)


RNP APCH - GPS.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. When local altimeter setting not received, use Lincoln altimeter setting increase LPV DA to 1110 feet and all visibilities ¼ SM. Increase LNAV/VNAV DA to 1168 feet and all visibilities ⅓ SM. Increase all MDAs 100 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ½ SM. Baro-VNAV and VDP NA when using Lincoln altimeter setting. For inop ALS, increase LPV all Cats visibility to 1⅓ SM, LNAV Cat A/B visibility to 1 SM and Cat C/D visibility to 1⅓ SM. For inop ALS when using Lincoln altimeter setting, increase LPV visibility all Cats to 1⅓ SM and LNAV Cat A/B visibility to 1 SM.

MALSR

MISSED APPROACH:
Climb to 2400 direct CASIP and hold.

ATIS 126.1 282.2	SAINT LOUIS APP CON 125.8 269.2	PEORIA TOWER 124.0 353.85	GND CON 121.85 348.6	CLNC DEL 124.675 317.55
----------------------------	---	-------------------------------------	--------------------------------	-----------------------------------



VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 57).				2400 ↑	CASIP ✦
4 NM Holding Pattern					
FAPSA					
EPEPE					
2500					
308° 128°					
GP 3.00° TCH 59					
2500					
1.3 NM to RW13					
RW13					
6 NM				4.3 NM	1.3
CATEGORY	A	B	C	D	
LPV DA	1025-¾		389 (400-¾)		
LNAV/ VNAV DA	1083-1		447 (500-1)		
LNAV MDA	1120-½	484 (500-½)	1120-1	484 (500-1)	
CIRCLING	1160-1	499 (500-1)	1180-1½ 519 (600-1½)	1400-2¼ 739 (800-2¼)	