

WAAS CH 86809 W27A	APP CRS 276°	Rwy Ldg 12000 TDZE 875 Apt Elev 896
--	------------------------	--

RNAV (GPS) Y RWY 27

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)


RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C or above 54°C. * RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 3000 direct SEMSE then on track 225° to AVIEW and hold.

D-ATIS 134.375	CINCINNATI APP CON 119.7 363.15 (090°-269°) 123.875 363.15 (270°-089°)	CINCINNATI TOWER 118.975 360.85 (18L/36R) 118.3 (9/27, 18C/36C) 133.325 (18R/36L)	GND CON 121.7
--------------------------	--	---	-------------------------



MISSD APCH FIX SEMSE

4 NM

066°

225° (15.2)

246°

AVIEW

(not to scale)

ELEV 896

TDZE 875

3000 SEMSE tr 225° AVIEW

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 67).

SOAND 2500 276° 3500

BLOCK 3500

GP 3.00° TCH 55

1.5 NM to RW27

1.5 NM 3.4 NM 3.6 NM

CATEGORY	A	B	C	D
LPV DA*	1075/24 200 (200-½)			
LNAV/VNAV DA	1320/45 445 (500-¾)			
LNAV MDA	1420/24 545 (600-½)	1420/60 545 (600-1¼)		
CIRCLING	1460-1 564 (600-1)	1560-1¾ 664 (700-1¾)	1560-2 664 (700-2)	

18L

18R

36L

36R

12001

10000 X 150

8000 X 150

0.35°

TWR

HIRL all Rwy's

TDZ/CL all Rwy's except 27