


LOC/DME I-RLE <u>111.5</u> Chan 52	APP CRS 259°	26L	26R
		Rwy Ldg 10526	12638
		TDZE 2069	2067
		Apt Elev 2181	2181

ILS Y or LOC Y RWY 26L
HARRY REID INTL (LAS)

RNP APCH - GPS.		MALSF Rwy 26L 	MALS Rwy 26R 	MISSED APPROACH: Climb to 3200 then dimbing right turn to 6000 heading 080° and on BLD R-286 to BLD VORTAC and hold, continue climb-in-hold to 6000.				
DME required.								
 Inop table does not apply to S-ILS 26L or Sidestep 26R. For inop ALS increase S-LOC 26L Cats C and D visibility to 1 3/8 SM.								
D-ATIS	LAS VEGAS APP CON		LAS VEGAS TOWER		GND CON		CLNC DEL	CPDLC
132.4	125.025 379.15 (West) 119.775 282.2 (East)		118.75 257.8 (Rwy 1L/19R, 1R/19L) 119.9 257.8 (Rwy 8L/26R, 8R/26L)		121.1 270.8 E of 1R/19L 121.9 254.3 W of 1L/19R			



3200	6000	BLD R-286	BLD	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 84).					BERBN
hdg 080°									
I-RLE 1.9		RELIN I-RLE 7.2	HUXAR I-RLE 11.8	KODSE	BISHP	HOGOG	079° 8000		
3800		3800	5000	5800	6600	7000	GS 3.00° TCH 60		
1.2 NM		4.1 NM	4.6 NM	2.6	2.7	1.4	3 NM		
CATEGORY	A			B		C		D	
S-ILS 26L	2269-3/4 200 (100-3/4)								
S-LOC 26L	2520-3/4 451 (400-3/4)					2520-1 451 (400-1)			
SIDESTEP 26R	2560-1 493 (400-1)					2560-1 1/2 493 (400-1 1/2)		2560-2 493 (400-2)	
CIRCLING	3020-1 1/4 839 (900-1 1/4)		3060-1 1/4 879 (900-1 1/4)		3100-2 3/4 919 (1000-2 3/4)		3540-3 1359 (1400-3)		

