WAAS CH 40430 W06A	APP CRS 056°	Rwy Ldg 5000 TDZE 405 Apt Elev 407

RNAV (GPS) RWY 6
OWENSBORO/DAVIESS COUNTY RGNL (OWB)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Rwy 6 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Evansville altimeter setting: increase LPV DA to 719 feet and all Cats visibility ⅛ mile; increase LNAV/VNAV DA to 734 feet and all Cats visibility ¼ mile; increase all MDA 60 feet and LNAV Cats C/D and Circling Cats C/D visibility ¼ mile. Baro-VNAV and VDP NA when using Evansville altimeter setting.

MISSED APPROACH: Climb to 3000 direct CINLI and hold.

AWOS-3PT	EVANSVILLE APP CON ★	OWENSBORO TOWER ★	GND CON	UNICOM
119.025	124.025 290.9	120.7 (CTAF) L 251.15	121.7	122.95





CATEGORY	A	B	C	D
LPV DA	660-⅞ 255 (300-⅞)			
LNAV/VNAV DA	675-⅞ 270 (300-⅞)			
LNAV MDA	800-1 395 (400-1)		800-1⅛ 395 (400-1⅛)	
CIRCLING	860-1 453 (500-1)	1120-1 713 (800-1)	1140-2 733 (800-2)	1140-2¼ 733 (800-2¼)

SE-1, 02 OCT 2025 to 30 OCT 2025