

LOC I-FTY 109.1	APP CRS 085°	Rwy Ldg TDZE Apt Elev	5797 808 841
---------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 8

FULTON COUNTY EXEC/CHARLIE BROWN FLD (F'TY)

RADAR required to define TALDE.
RADAR required for procedure entry.

▼ Circling Rwy 14, 32 NA at night. Rwy 8 helicopter visibility reduction below ¾ SM NA.
▲ For inop ALS, increase S-LOC 8 Cat A visibility to 1 SM, Cat C/D visibility to 2 ½ SM.
Ridge with trees to 1299' MSL between FAF and runway threshold may be obscured by clouds even with airfield ceiling at or above procedure minimums.

MALSR

MISSED APPROACH: Climb to 1800 then climbing left turn to 4000 on heading 290° and RMG R-132 to DALAS INT/ RMG VORTAC 18.5 DME and hold.

ATIS 120.175	ATLANTA APP CON 121.0 268.7	FULTON COUNTY TOWER 118.45 257.8	GND CON 121.7 348.6
------------------------	---------------------------------------	--	-------------------------------

One Minute Holding Pattern

CAVEB INT RADAR

6000
3000

← 265°
→ 085°

GS 3.00°
TCH 63

1800
4000

hdg
290°

TALDE RADAR

2800

*LOC only.

5797 X 100

4118 X 100

1.0% UP

TWR

5797

085°

9.5 NM

6.1 NM

CATEGORY	A	B	C	D
S-ILS 8	1058-½ 250 (300-½)			
S-LOC 8	1640-¾ 832 (800-¾)		1640-1⅞ 832 (800-1⅞)	
CIRCLING	1640-1 799 (800-1)	1640-1¼ 799 (800-1¼)	1740-2¾ 899 (900-2¾)	1740-3 899 (900-3)

HIRL Rwy 8-26
REIL Rwys 14, 26

FAF to MAP 6.1 NM

Knots	60	90	120	150	180
Min:Sec	6:06	4:04	3:03	2:26	2:02

ATLANTA, GEORGIA
Amdt 18 30JAN20

FULTON COUNTY EXEC/CHARLIE BROWN FLD (F'TY)

33°47'N-84°31'W

ILS or LOC RWY 8

SE-4, 02 OCT 2025 to 30 OCT 2025

SE-4, 02 OCT 2025 to 30 OCT 2025