

WAAS CH 78311 W17A	APP CRS 172°	Rwy Ldg TDZE 248 Apt Elev 250
--	------------------------	---

RNAV (GPS) RWY 17

CORVALLIS MUNI (CVO)



RNP APCH - GPS.

Circling Rwy 28 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, procedure NA. For inop ALS, increase LNAV Cat C/D visibility to 1¼ SM.

MALSR

MISSED APPROACH: Climb to 1100 then climbing left turn to 3700 direct INNOP and hold, continue climb-in-hold to 3700.

AWOS-3PT 135.775	CASCADE APP CON ★ 127.5 348.7	UNICOM 123.075 (CTAF) 0
----------------------------	---	--



1100	3700	INNOP	INNOP	4 NM Holding Pattern
ACVOL	EGBEW	INNOP		
CAYJU 2.5 NM to RW17	2400	2900	352°	6000 3700
1.8 NM to RW17	1080	2400	172°	GP 3.00° TCH 45
1.8 NM	0.7	4.1 NM	2 NM	3.9 NM
CATEGORY	A	B	C	D
LPV DA	448-½	200 (200-½)		
LNAV/VNAV DA	571-½	323 (400-½)		
LNAV MDA	880-½	632 (700-½)	880-1⅓	632 (700-1⅓)
CIRCLING	880-1	630 (700-1)	920-1¾	1080-2¾
			670 (700-1¾)	830 (900-2¾)

NW-1, 02 OCT 2025 to 30 OCT 2025

NW-1, 02 OCT 2025 to 30 OCT 2025