

APP CRS
101°

Rwy Ldg
TDZE
Apt Elev

8016
10
10

RNAV (GPS) RWY 10

LUIS MUNOZ MARIN INTL (SJU)(TJSJ)

WAAS VNAV NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop MALSR, increase LNAV/VNAV visibility all Cats to 1¼ and increase LNAV Cats C/D visibility to 1⅓.

MALSR

MISSED APPROACH: Climb to 500 then descending left turn to 3000 direct DEEDY and hold.

D-ATIS	SAN JUAN APP CON		SAN JUAN TOWER		GND CON	CLNC DEL	CPDLC
125.8	119.4	269.2	(WEST & SW) 120.9 290.2 (NORTH & EAST)	132.05 257.8	121.9 348.6	126.4 284.6	

Procedure NA for arrival at CORAF on route 6 northwest bound and G432 northbound.

(IAF) CORAF

2200 NoPT (16.7)

6 NM

184°

004°

DEEDY

MSA RW10 25 NM

5100

4 NM

281°

101°

1500 (6.1)

(FAF) REMSY

321

109±

217

297

448

ZASPU 1.7 NM to RW10

Δ 336

Δ 365±

Δ 421

798

734±

898

Procedure NA for arrival at VARN A on routes 10 and 12 southwest bound and G449 southeast bound.

(IAF) VARN A

3500 NoPT (5.4)

054°

YIGTO

2300

054°

(IF/IAF) TNNER

1604

1961

4 NM Holding Pattern TNNER

2300

281°

101°

GP 3.00° TCH 52

1500

101°

REMSY

1500

ZASPU 1.7 NM to RW10

*600

500

3000

DEEDY

* LNAV only

10400 X 193

TWR

8016 X 150

28

101°

CATEGORY	A	B	C	D
LNAV/VNAV DA	408-7/8 398 (400-7/8)			
LNAV MDA	480-1/2	470 (500-1/2)	480-1	470 (500-1)
CIRCLING	600-1	590 (600-1)	740-2 730 (800-2)	920-3 910 (1000-3)

REIL Rwy 26

HIRL Rwys 8-26 and 10-28

SAN JUAN, PUERTO RICO

LUIS MUNOZ MARIN INTL (SJU)(TJSJ)

RNAV (GPS) RWY 10

Amdt 2B 05NOV20

18°26'N-66°00'W