

HARLINGEN, TEXAS

AL-827 (FAA)

25275

VOR/DME HRL <u>113.65</u> Chan 83 (Y)	APP CRS 160°	Rwy Ldg TDZE Apt Elev	9400 35 36
---	------------------------	-----------------------------	---------------------------------------

VOR RWY 18R
VALLEY INTL (HRL)


DME required.

T For inop ALS, increase S-18R Cat C/D visibility to 1½ SM. When local altimeter setting not received, use Port Isabel altimeter setting and increase all MDAs 60 feet and S-18R visibility Cat C/D to RVR 5500 and Circling visibility Cat C/D ¼ SM. VPD NA when using Port Isabel altimeter setting.

MALSR

MISSED APPROACH: Climb to 1200 then climbing right turn to 2000 direct HRL VOR/DME and hold, continue to climb in hold to 2000.

ATIS 124.85	VALLEY APP CON 120.7 279.5	HARLINGEN TOWER ★ 119.3(CTAF) 0 317.6	GND CON 121.7	UNICOM 122.95
-----------------------	--------------------------------------	---	-------------------------	-------------------------



VGSI and descent angles not
(VGSI Angle 3.00/TCH 71).

MOVBE

1200

200

HR

Remain
within 10 NM

Remain
in 10 NM

2000

340°


160°

1600

CALA

1.8

CATEGORY	A	B	C	D
S-18R	440/24	405 (500-½)	440/40	405 (500-¾)
CIRCLING	460-1 424 (500-1)	560-1 524 (600-1)	600-1½ 564 (600-1½)	680-2 644 (700-2)



HARLINGEN, TEXAS

Amdt 1 11JUL24

26°14'N-97°39'W

VALLEY INTL (HRL)

VOR RWY 18R

SC-3, 02 OCT 2025 to 30 OCT 2025