

LOC/DME I-HCV
110.3
Chan **40**

APP CRS
052°

Rwy Ldg
TDZE
Apt Elev
6215
947
947

ILS or LOC RWY 5
WEST VIRGINIA INTL YEAGER (CRW)

Autopilot coupled approach NA below 1300.

MISSED APPROACH: Climb to 1800 then climbing left turn to 3500 direct HVQ VOR/DME and hold.

ATIS
127.6

CHARLESTON APP CON
124.1 269.125

CHARLESTON TOWER
125.7 257.8

GND CON
121.8 348.6

		ELEV 947		D		TDZE 947						
One Minute Holding Pattern		SHOAL INT I-HCV 11.9 RADAR		KANCO INT I-HCV 6 RADAR		ZEVUR INT I-HCV 2.1						
5400 3500		2900		1640		1800 3500 HVQ						
GS 3.00° TCH 56		5.9 NM		3.9 NM		1 NM 1 NM 0.1						
CATEGORY	A	B	C	D								
S-ILS 5	1197/40		250 (300-¾)									
S-LOC 5	1640/55	693 (700-1)	1640-2	693 (700-2)								
CIRCLING	1640-1	693 (700-1)	1760-2½ 813 (900-2½)	1880-3 933 (1000-3)								
ZEVUR FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)												
S-LOC 5	1320/55		373 (400-1)									
CIRCLING	1600-1	653 (700-1)	1760-2½ 813 (900-2½)	1880-3 933 (1000-3)								
CHARLESTON, WEST VIRGINIA				WEST VIRGINIA INTL YEAGER (CRW)								
Orig-B 05OCT23				38°23'N-81°36'W								
				ILS or LOC RWY 5								

NE-4, 02 OCT 2025 to 30 OCT 2025