



WAAS CH 45703 W29A	APP CRS 287°	Rwy Ldg 5155 TDZE 42 Apt Elev 42
--	------------------------	---

RNAV (GPS) RWY 29

LAFAYETTE RGNL/PAUL FOURNET FLD (L.F'T')

RNP APCH.		MISSED APPROACH: Climb to 2800 direct SUVDE and on track 273° to RAYNE and hold.
T A	Rwy 29 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -2°C or above 54°C.	

ATIS 134.05	LAFAYETTE APP CON ★ 121.1 363.0	LAFAYETTE TOWER ★ 118.5 (CTAF) 0 257.8	GND CON 121.8	UNICOM 122.95
-----------------------	---	--	-------------------------	-------------------------



2800		SUVDE	fr 273°	RAYNE	5 NM Holding Pattern	
*LNAV only.		TODNE 2.5 NM to RW29	ATCHA 1700	SPILL		GP 3.00° TCH 51
*0.9 NM to RW29		*880	1700	107° → 6000 ← 287° 2100		
0.9		1.6	2.6 NM	6 NM		
CATEGORY	A		B		C	D
LPV DA	292-¾		250 (300-¾)			
LNAV/VNAV DA	292-¾		250 (300-¾)			
LNAV MDA	380-1		338 (400-1)			
CIRCLING	500-1 458 (500-1)	580-1 538 (600-1)	700-1¾ 658 (700-1¾)	700-2 658 (700-2)		