

WAAS CH 87019 W32A	APP CRS 325°	Rwy Idg TDZE Apt Elev	6306 2120 2143
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 32

BRADFORD RGNL (BFD)


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using St. Marys altimeter setting. DME/DME RNP-0.3 NA. Inop table does not apply to LPV and LNAV Cats A/B. For inop MALS, increase LNAV/VNAV all Cats visibility to 1½ mile and LNAV Cats C/D visibility to 1¼ mile. When local altimeter setting not received, use St. Marys altimeter setting: increase LPV DA to 2455 feet; increase LNAV/VNAV DA to 2685 feet and all visibilities ½ SM; increase all MDAs 100 feet and Circling Cat C visibility ½ SM and Cat D ¼ SM. For inop MALS, when using St. Marys altimeter setting, increase LPV all Cats visibility to 1½ mile.

MALS


MISSED APPROACH:

Climb to 4500 direct KONBE and hold.

ASOS 133.825	CLEVELAND CENTER 124.325 353.85	UNICOM 123.075 (CTAF) 0
------------------------	---	-----------------------------------



ELEV 2143	D	TDZE 2120
-----------	----------	-----------



MIRL Rwy 5-23 **0**
HIRL Rwy 14-32 **0**
REIL Rwy 5, 14 and 23 **0**

4500 KONBE		JARVO		NIMEE		5 NM Holding Pattern
*LNAV only.		*1.2 NM to RW32		4000		GP 3.00° TCH 52
1.2 NM		4.5 NM		6.1 NM		
CATEGORY	A	B	C	D		
LPV DA	2370-1		250 (300-1)			
LNAV/VNAV DA	2600-1½		480 (500-1½)			
LNAV MDA	2540-1		420 (400-1)			
CIRCLING	2620-1	477 (500-1)	2720-1½ 577 (600-1½)	2760-2 617 (700-2)		