

WAAS

CH **65621**

W04A

APP CRS

045°

Rwy Idg

5130

TDZE

51

Apt Elev

53

RNAV (GPS) RWY 4

DELAWARE COASTAL (GED)

RNP APCH - GPS.

▼

Rwy 4 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats and LNAV Cats C/D visibility $\frac{1}{4}$ mile.

MALS

MISSED APPROACH: Climb to 2000 direct HUVOX and hold.

ASOS 118.375	DOVER APP CON 132.425 257.875	GCO 125.55	UNICOM 123.0 (CTAF)
------------------------	---	----------------------	-------------------------------

30 NM to ZARVI

2100

135°

ZARVI

315°

2000

2100

30 NM to ZARVI (NoPT)

1048

R-4006

260

176

205

RW04

(FAF) SABER

2000

045°

(7)

(IF/IAF) ZARVI

045°

225°

4 NM

MISSED APCH FIX

4 NM

045°

225°

HUVOX

4 NM Holding Pattern

ZARVI

SABER

2000

HUVOX

2000

GP 3.00°

TCH 45

225°

045°

045°

2000

*1.3 NM to RW04

*LNAV only.

RW04

7 NM

4.7 NM

1.3 NM

CATEGORY	A	B	C	D
LPV DA	355- $\frac{3}{4}$		304 (400- $\frac{3}{4}$)	
LNAV/VNAV DA	503-1 $\frac{1}{4}$		452 (500-1 $\frac{1}{4}$)	
LNAV MDA	520- $\frac{3}{4}$	469 (500- $\frac{3}{4}$)	520-1 $\frac{1}{8}$	469 (500-1 $\frac{1}{8}$)
CIRCLING	560-1 507 (600-1)	580-1 527 (600-1)	720-1 $\frac{3}{4}$ 667 (700-1 $\frac{3}{4}$)	720-2 667 (700-2)

ELEV 53

TDZE 51

REIL Rwy 4, 22, 10, and 28

MIRL Rwy 4-22 and 10-28

GEORGETOWN, DELAWARE

Amtd 3A 29DEC22

38°41'N-75°22'W

DELAWARE COASTAL (GED)

RNAV (GPS) RWY 4