

TOP ALTITUDE:
ASSIGNED AT ATC

RNAV-1 DME/DME/IRU or GPS.
RADAR required.



IIICE



KAYLN
(15)




MTRCT
(13)




1800

TAKEOFF MINIMUMS:
Rwy 4, 17, 22: Standard.
Rwy 35: Standard with minimum climb
of 500' per NM to 1100.

DETROIT DEP CON
134.3 284.0
AWOS-3
119.675
CTAF
123.0



N



NOTE: Turbojet departures at/above 10000,
maintain 280K until advised by ATC.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 4: Climb on heading 037° to 1200 then as assigned by ATC, thence....
TAKEOFF RUNWAY 17: Climb on heading 174° or as assigned by ATC, thence....
TAKEOFF RUNWAY 22: Climb on heading 217° or as assigned by ATC, thence....
TAKEOFF RUNWAY 35: Climb on heading 006° to 1800 then as assigned by ATC, thence....
....for RADAR vectors to MTRCT, then on track 279° to KAYLN, then on (transition). Maintain ATC assigned altitude,
expect filed altitude 10 minutes after departure.
SMUUV TRANSITION (KAYLN3.SMUUV):