

WAAS CH 61399 W10A	APP CRS 108°	Rwy Ldg TDZE 337 Apt Elev 342
--	------------------------	---

RNAV (GPS) RWY 10

CAPE GIRARDEAU RGNL (CGI)

RNP APCH - GPS.			MALSR	MISSED APPROACH: Climb to 3000 direct FISAV and hold.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Cairo altimeter setting and increase LPV DA to 585 feet, LNAV/VNAV DA to 761 feet, and all visibilities 1⁄8 SM. Increase all MDAs 60 feet and LNAV Cat C/D visibility 1⁄8 SM, and Circling Cats C/D visibility to 1⁄4 SM. Baro-VNAV and VDP NA when using Cairo Rgnl altimeter setting. For inop ALS, increase LNAV/VNAV visibility all Cats and LNAV visibility Cat C/D to 1 SM. For inop ALS, when using Cairo altimeter setting, increase LNAV/VNAV all Cats and LNAV Cat C/D visibility to 1 SM.				
ASOS 120.55	MEMPHIS CENTER 133.65 292.15	CAPE GIRARDEAU TOWER★ 125.525 (CTAF) 0	GND CON 124.7	UNICOM 122.95

