

WAAS CH 90530 W36A	APP CRS 358°	Rwy Ldg TDZE 894 Apt Elev 894
--	------------------------	---

RNAV (GPS) RWY 36

BUTLER MEML (BUM)

RNP APCH.


▼

▲NA

Baro-VNAV NA. Use Clinton altimeter setting; when not received, use Kansas City Downtown/Wheeler Fld altimeter setting and increase all DA/MDA 60 feet, increase LPV and LNAV/VNAV all Cats visibility ¼ mile. Rwy 36 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 3000 direct LADSY and hold.

KANSAS CITY CENTER 125.55 327.0	CTAF 122.9
---	----------------------



4 NM Holding Pattern

GP 3.00° TCH 36

178°

358°

358°

2500

CEKBO

2500

3000

LADSY

6 NM

4.9 NM

RW36

CATEGORY	A	B	C	D
LPV DA	1226-1⅛	332 (400-1⅛)	NA	
LNAV/VNAV DA	1523-2¼	629 (700-2¼)	NA	
LNAV MDA	1640-1 746 (800-1)	1640-1¼ 746 (800-1¼)	NA	

ELEV 894

TDZE 894

81

3999 X 7.5

36

358°

MIRL Rwy 18-36

NC-3, 02 OCT 2025 to 30 OCT 2025

NC-3, 02 OCT 2025 to 30 OCT 2025