

APP CRS
222°

Rwy Ldg
TDZE
334

Apt Elev
338

RNAV (GPS) RWY 22

DYERSBURG RGNL (DYR)

RNP APCH - GPS.

When local altimeter setting not received, use HKA altimeter setting and increase all MDAs 60 feet and visibility Cats C and D ¼ SM. VDP NA with HKA altimeter setting.

MISSED APPROACH: Climb to 2900 direct RUQAW and hold.

AWOS-3PT 135.625	MEMPHIS CENTER 134.65 316.15	UNICOM 123.05 (CTAF) 0
----------------------------	--	----------------------------------

MISSED APCH FIX
RUQAW

2900

RUQAW

ELEV 338

TDZE 334

91°

222°

400 X 74

568 X 98

0.3% UP

0.8% UP

2900

RUQAW

1.2 NM

1.2 NM

2.7 NM

6.8 NM

DAKNE

CAGAC

AYODO

4 NM Holding Pattern

1.2 NM to RW22

3.02° TCH 30

2000

1140

042°

222°

6000

2900

CATEGORY	A	B	C	D
LNAV MDA	740-1	406 (500-1)	740-1½	406 (500-1½)
CIRCLING	760-1 422 (500-1)	800-1 462 (500-1)	1040-2 702 (800-2)	1240-3 902 (1000-3)

MRL Rwy 4-22 0

REIL Rwy 4 and 22 0

DYERSBURG, TENNESSEE

Amdt 1D 12JUN25

36°00'N-89°24'W

DYERSBURG RGNL (DYR)

RNAV (GPS) RWY 22