

LOC/DME I-ANI

109.7

Chan 34

APP CRS

109°

Rwy Idg

5400

TDZE

97

Apt Elev

97

ILS or LOC RWY 11

ANIAK (ANI)(PANI)

DME required.

▼

▲

❄

Circling NA north of Rwy 11-29. Rwy 11 helicopter visibility reduction below ¾ SM NA. Inop table does not apply to S-ILS all Cats.

-37°C

MALSF

⬇

⬆

MISSED APPROACH: Climb to 1500 then climbing right turn to 3500 direct ANI NDB and hold, continue climb-in-hold to 3500. (ADF required)

AWOS-3P 124.3	ANCHORAGE CENTER 118.15 251.05	CLNC DEL 118.15	CTAF 122.10
------------------	-----------------------------------	--------------------	----------------

ILS unusable from I-ANI 1.7 DME inbound.

One Minute Holding Pattern

IKUFU I-ANI 11.7

ANORE I-ANI 6

CALIL I-ANI 4.4

I-ANI 3.2

ZUSEK I-ANI 1.7

GS 3.00° TCH 35

5.7 NM 1.6 NM 1.2 NM 1.5 NM 0.6

1500 3500 ANI

*LOC only.

109° 6200 X 100 138

CATEGORY	A	B	C	D
S-ILS 11	347-¾ 250 (300-¾)			
S-LOC 11	800-¾ 703 (800-¾)		800-1¾ 703 (800-1¾)	
CIRCLING	800-1 703 (800-1)		860-2¼ 763 (800-2¼)	1200-3 1103 (1200-3)

HIRL Rwy 11-29

ANIAK, ALASKA

Amdt 1 10SEP20

61°35'N-159°33'W

ANIAK (ANI)(PANI)

ILS or LOC RWY 11