


APP CRS	Rwy Ldg	11050
023°	TDZE	439
	Apt Elev	439

RNAV (RNP) Z RWY 2L
FAIRBANKS INTL (FAI) (PAFA)

RNP AR APCH - GPS. ⚠ -29°C For uncompensated Baro-VNAV systems, procedure NA below -19°C or above 54°C. For inop ALS, increase RNP 0.10* all Cats visibility to RVR 4500, increase RNP 0.10 all Cats visibility to RVR 5500, and increase RNP 0.30 all Cats visibility to RVR 6000.	ALSf-2 ⚠	MISSED APPROACH: Climb to 5000 on track 023° USAZY then right turn to ODIFU and track 184° to KRNL and hold. *Missed approach requires minimum climb of 222 feet per NM to 2420.
---	-------------	---

ATIS 124.4	FAIRBANKS APP CON 125.35 363.2	FAIRBANKS TOWER 118.3 257.8	GND CON 121.9	CLNC DEL 127.6
---------------	-----------------------------------	--------------------------------	------------------	-------------------



See planview for multiple IF locations.		5000 USAZY		ODIFU tr 184°		KRNL	
JIRIG		HONUT		RW02L			
2200		1600		1600			
GP 3.00°		TCH 56		VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 73).			
2.1 NM		3.5 NM					
CATEGORY	A	B	C	D			
RNP 0.10 DA*	755/24 316 (400-½)						
RNP 0.10 DA	805/35 366 (400-¾)						
RNP 0.30 DA	855/40 416 (500-¾)						
AUTHORIZATION REQUIRED							

