

WAAS
CH **69404**
W02A

APP CRS
016°

Rwy Ldg
TDZE **94**
Apt Elev **100**

RNP APCH.

Baro-VNAV NA when using Soldotna altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). When local altimeter setting not received, use Soldotna altimeter setting: increase LPV DA to 366 feet and LNAV/VNAV DA to 429 feet and all MDA 40 feet; increase LPV and LNAV/VNAV visibility all Cats and LNAV Cat C/D visibility ½ mile; increase Circling Cat D visibility ¼ mile. VDP NA when using Soldotna altimeter setting. Circling Rwy 2R, 20L NA at night. Circling Rwy 2W, 20W NA.

MISSED APPROACH:
Climb to 2000 direct TBONE and hold.

RNAV (GPS) RWY 2L
KENAI MUNI (ENA) (PAEN)

ATIS
133.35

ANCHORAGE CENTER
125.7 379.1

KENAI TOWER*
121.3 (CTAF) 239.3

GND CON
118.75

KENAI RADIO
122.65

Procedure NA for arrivals on ENA VOR/DME airway radials 198 CW 260.

2000 NoPT 087° (9.7) (IAF) ACIGE

5 NM 196° 016° (IF/IAF) FOPTY

1700 016° (6.1) (FAF) CAPRU

2000 NoPT 213° (6.7) (IAF) KASSI

223 RWY02L

2000 to FOPTY 196° (14.6)

KENAI ENA

MSA RW02L 25 NM 3500

5 NM Holding Pattern

FOPTY

2000

196°

016°

GP 3.00° TCH 53

CAPRU

1700

016°

1700

6.1 NM

3.8 NM

1.1 NM

2000 TBONE

* LNAV only

* 1.1 NM to RW02L

RW02L

CATEGORY	A	B	C	D
LPV DA	344-¾ 250 (300-¾)			
LNAV/VNAV DA	407-1 313 (400-1)			
LNAV MDA	480-1 386 (400-1)		480-1½ 386 (400-1½)	
CIRCLING	560-1 460 (500-1)	580-1 480 (500-1)	580-1½ 480 (500-1½)	740-2 640 (700-2)

ELEV 100

TDZE 94

20W

20L

20R

4600 X 240

1980 X 75

7835 X 130

TWR

REIL Rwy 2L

HIRL Rwy 2L-20R

KENAI, ALASKA
Amdt 3A 13SEP18

60°34'N-151°15'W

KENAI MUNI (ENA) (PAEN)

RNAV (GPS) RWY 2L