

KING SALMON, ALASKA

HI-ILS Z or LOC Z RWY 12

LOC/DME I-AKN

110.3

Chan 40

APCH CRS

121°

Rwy Idg

8501

TDZE

62

Arpt Elev

73

[USAF]

KING SALMON (AKN) (PAKN)

DME required. RADAR required for procedure entry.

MALSR

A5

MISSED APPROACH: Climb to 600, then climbing right turn to 3000 via heading 240° and AKN VORTAC R-210 to OLLER/AKN 15 DME and hold.

ATIS

128.8

ANCHORAGE CENTER

124.8 354.0

TOWER★

118.3 279.5

GND CON

121.9

CTAF

121.90 352.05

UNICOM

122.95

†When control tower closed, increase RVR to 50.
Autopilot coupled approaches not authorized below 700' MSL.

NOVET RADAR

30

FL200

116°

Intcp Lczt

NIRRI

I-AKN

15.3

KINKE

I-AKN

6.6

ZOPUB

I-AKN

3

OLLER

AKN

15

Use I-AKN DME when on localizer course

GS 3.00°

TCH 66

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM

1.3 NM

600

3000

hdg 240°

Intcp

AKN

R-210

OLLER

AKN

15

172

121°

81

70±

4017

8900

150

100±

36

TWR

A5

P

P

3

1.6

1700

560

3.6 NM