

VORTAC BAE

116.4

Chan 111

APP CRS

153°

Rwy Idg

TDZE

Apt Elev

N/A

N/A

911

VOR-A

WAUKESHA COUNTY (UES)

▼

▲

When local altimeter setting not received, use Lawrence J Timmerman altimeter setting; increase all MDAs 60 feet and increase Circling Cat C and D visibility ¼ SM.

MISSED APPROACH: Climb to 2000, then climbing right turn to 2800 direct BAE VORTAC and hold.

ATIS

118.875

MILWAUKEE APP CON

125.35 307.0

WAUKESHA TOWER ★

123.7 (CTAF)

GND CON

121.6

CLNC DEL

121.6


CLNC DEL

128.7

(When twr closed)

UNICOM

122.95



Remain within 10 NM

BAE VORTAC

2000

2800

BAE

2800

333°

153°

2800

MAFIW BAE 4.6

4.6 NM

ELEV 911

153°

01

81

5849 X 100

3599 X 75

36

28

36

960

960

HIRL Rwy 10-28

MIRL Rwy 18-36

REIL Rwy 28

REIL Rwy 18 and 36

CATEGORY	A	B	C	D	FAF to MAP 4.6 NM					
CIRCLING	1460-1 549 (600-1)	1500-1 589 (600-1)	1540-1¾ 629 (700-1¾)	1640-2¼ 729 (800-2¼)	Knots	60	90	120	150	180
					Min:Sec	4:36	3:04	2:18	1:50	1:32