ASSIGNED BY ATC

CONLE FIVE DEPARTURE (RNAV)

POTOMAC DEP CON 126.1 338.25 RADAR required.

TOP ALTITUDE:

OHSSS 11000

14000

CLNC DEL 127.425 126.9 (when tw

ATIS 124.875

126.9 (when twr closed) GND CON

127.425 FREDERICK TOWER ★ 132.4 (CTAF) 1100 1240 900

TAKEOFF MINIMUMS:

Rwy 5: 400-3 or standard with minimum climb of 255' per NM to 600.


Rwy 12: 500-234 or standard with minimum climb of 410′ per NM to 800.

Rwy 23: Standard.

Rwy 30: Standard with minimum climb of 340'

per NM to 2400.

NOTE: Jet aircraft only.





to 30 OCT 2025

02 OCT 2025

NOTE: Chart not to scale.

V

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 5: Climb on heading 048° to 1100 before turning left.

TAKEOFF RUNWAY 12: Climb on heading 124° to 900 before proceeding westbound.

TAKEOFF RUNWAY 23: Climb on heading 229° to 1200 before turning right.

Climb on assigned heading for RADAR vectors to cross OHSSS at or above 11000, then on track 212° to cross CONLE at or below 14000, then on assigned transition. Maintain ATC assigned altitude. Expect clearance to filed altitude within 10 minutes after departure.

COLIN TRANSITION (CONLES.COLIN) SCOOB TRANSITION (CONLES.SCOOB)