

LOC I-DLX <u>111.3</u>	APP CRS 191°	Rwy Idg 11089 TDZE 272 Apt Elev 312
----------------------------------	------------------------	--

ILS RWY 19C (CAT II & III)
WASHINGTON DULLES INTL (IAD)

RNP APCH - GPS.

RADAR required for procedure entry at NOOXX. DME or RADAR required.


T Simultaneous approach authorized. DME from AML VOR/DME. DME use requires simultaneous reception of I-DLX and AML DME.

ALSF-2

MISSED APPROACH:
Climb to 3000 direct
MOOOV and hold.

D-ATIS	POTOMAC APP CON	DULLES TOWER	GND CON
134.85	120.45 306.925 (241°-330°)	120.1 317.8 (Rwy 1R/19L)	121.9 317.8 (EAST)
	128.525 306.925 (091°-240°)	120.25 348.6 (Rwy 1C/19C)	121.625 348.6 (WEST)
	126.1 338.25 (331°-090°)	134.425 348.6 (Rwys 1L/19R and 12/30)	

CLNC DEL 135.7 317.8	CPDLC
--------------------------------	-------



VGSI and ILS glidepath not coincident
(VGSI Angle 3.00/TCH 72).

CATEGORY	A	B	C	D
S-ILS 19C		CAT II RA 110/12 100 DA 372		
S-ILS 19C		CAT IIIa RVR 07		
S-ILS 19C		CAT IIIb RVR 06		
S-ILS 19C		CAT IIIc NA		

**CATEGORY II & III ILS - SPECIAL AIRCREW
& AIRCRAFT CERTIFICATION REQUIRED**