30 OCT 2025

2

02 OCT 2025

EC-3,

CARYN SEVEN DEPARTURE (RNAV) CHICAGO DEP CON **TOP ALTITUDE:** 133.5 349.0 3000 **ATIS** 1260 132.075 1260 **GND CON** 121.8 1260 **DUPAGE TOWER** 120.9 257.8 1260 260 1260 260 **CMSKY** NOTE: Turbojet departures maintain 250K until advised by ATC. **CARYN** DPA 25 Ny TAKEOFF MINIMUMS: Rwys 2L/R, 10, 20L/R, 28, 33: Standard. 5000 2200 80° 56) Rwy 15: 300-1% or standard with minimum climb 3400 of 205' per NM to 1000. RNAV 1 - DME/DME/IRU or GPS. RADAR required. NOTE: Chart not to scale. - CYBIL RADAR required for non-GPS equipped aircraft.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 2L/R: Climb on heading 015° to 1260, then as assigned by ATC, for vectors to CMSKY, thence....

TAKEOFF RUNWAY 10: Climb on heading 097° to 1260, then as assigned by ATC, for vectors to CMSKY, thence....

TAKEOFF RUNWAY 15: Climb on heading 149° to 1260, then as assigned by ATC, for vectors to CMSKY, thence....

TAKEOFF RUNWAYS 20L/R: Climb on heading 195° to 1260, then as assigned by ATC, for vectors to CMSKY, thence....

TAKEOFF RUNWAY 28: Climb on heading 277° to 1260, then as assigned by ATC, for vectors to CMSKY, thence....

TAKEOFF RUNWAY 33: Climb on heading 329° to 1260, then as assigned by ATC, for vectors to CMSKY, thence....

....on track 185° to CARYN, then on (transition), maintain 3000. Expect filed altitude 10 minutes after departure.

CYBIL TRANSITION (CARYN7.CYBIL):