

LOC/DME I-TNQ	APP CRS	Rwy Ldg	5999
108.7	034°	TDZE	624
Chan 24		Apt Elev	625

ILS or LOC RWY 3

MENOMINEE RGNL (MNM)

DME required.

Autopilot coupled approach NA below 1830. Circling Rwy 14, 32 NA at night. Rwy 3 helicopter visibility reduction below ¾ SM NA. Inop table does not apply to S-ILS 3 all Cats and S-LOC 3 Cats A and B. For inop ALS, increase S-LOC 3 Cats C and D visibility to 1 ½ SM.

MALSR

MISSED APPROACH: Climb to 1700 then climbing left turn to 2600 on heading 180° and GRB R-036 to ILHUP/I-TNQ 16 DME and hold.

AWOS-3PT	GREEN BAY APP CON ★	UNICOM
121.45	120.3 338.2	122.8 (CTAF) 0

5 NM Holding Pattern			
ILHUP I-TNQ 16			
FABOM I-TNQ 6			
I-TNQ 2.5			
I-TNQ 1.2			
GS 3.00° TCH 50			
10 NM 3.5 NM 1.3 NM			
CATEGORY	A	B	C
S-ILS 3	900-1		276 (300-1)
S-LOC 3	1080-1		456 (500-1)
CIRCLING	1200-1 575 (600-1)		1200-1½ 575 (600-1½)
			1380-2½ 755 (800-2½)

MENOMINEE, MICHIGAN

Amtd 4A 02OCT25

45°08'N-87°38'W

MENOMINEE RGNL (MNM)

ILS or LOC RWY 3