



WAAS CH 65722 W31A	APP CRS 310°	Rwy Ldg 6758 TDZE 1345 Apt Elev 1354
--	------------------------	---

RNAV (GPS) RWY 31
RANGE RGNL (HIB)

RNP APCH - GPS.		 MALSR	MISSED APPROACH: Climb to 3500 direct FENOK and hold.
  -40°C	Baro-VNAV and VDP NA when using Eveleth altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Eveleth altimeter setting and increase LPV DA to 1581 feet; increase LNAV/VNAV DA to 1643 feet; increase all MDAs 40 feet; and Circling visibility Cat C ¼ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM, LNAV Cat C/D to 1 SM. For inop ALS when using Eveleth altimeter setting, increase LNAV/VNAV all Cats visibility to ¾ SM.		
ASOS 126.425	DULUTH APP CON 125.45 233.7	UNICOM 123.0 (CTAF) 	



ELEV 1354	D	TDZE 1345
-----------	----------	-----------



3500 FENOK

VGSI and RNAV glidepath not coincident (VGSI Angle 2.90/TCH 62).

CEKSA 6 NM Holding Pattern

HIBDA 1.5 NM to RW31

AYADO 3300

1 NM to RW31

130° 12000

310° 3500

3300

GP 3.00° TCH 55

1 NM 0.5 4.5 NM 7 NM

CATEGORY	A	B	C	D
LPV DA	1545-½	200 (200-½)		
RNAV/DA	1607-½	262 (300-½)		
RNAV MDA	1700-½ 355 (400-½)		1700-⅝ 355 (400-⅝)	
CIRCLING	1900-1 546 (600-1)	1920-1½ 566 (600-1½)		1980-2 626 (700-2)

RNAV (GPS) RWY 31