

SPRING FIVE DEPARTURE

AL-5165 (FAA)

SPRINGDALE MUNI (ASG)
SPRINGDALE, ARKANSAS

GND CON

121.6

SPRINGDALE TOWER ★

118.2 (CTAF)

AWOS-3

124.675

RAZORBACK DEP CON ★

126.6 305.2

MEMPHIS CENTER

126.1 269.0

UNICOM

122.95

TOP ALTITUDE:
4000

BARTLESVILLE

117.9 BVO

Chan 126

SPRINGFIELD

116.9 SGF

Chan 116

DOGWOOD

109.4 DGD

Chan 31

RAZORBACK

116.4 RZC

Chan 111

TULSA

114.4 TUL

Chan 91

OKMULGEE

114.9 OKM

Chan 96

WILL ROGERS

114.1 IRW

Chan 88

FORT SMITH

110.4 FSM

Chan 41

LITTLE ROCK

113.9 LIT

Chan 86

HOT SPRINGS

110.0 HOT

Chan 37

TAKEOFF MINIMUMS

Rwy 18: Standard.

Rwy 36: 400-2½ or standard with minimum
climb of 332' per NM to 1900.

NOTE: RADAR required.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 18: Climb on heading 183° to 1900, then turn left heading 120°,
thence

TAKEOFF RUNWAY 36: Climb on heading 003°, thence

. . . . Expect radar vectors to filed/assigned route. Climb and maintain 4000.
Expect clearance to filed altitude/flight level ten minutes after departure.

LOST COMMUNICATIONS: If communications are not established within 2 minutes
after departure, climb and maintain 5000' and proceed direct RZC VORTAC, then
proceed on course.

SPRING FIVE DEPARTURE