

WAAS CH 82018 W05A	APP CRS 050°	Rwy Ldg TDZE 1224 Apt Elev 1232
--	------------------------	---


RNAV (GPS) RWY 5

BRainerd Lakes RGNL (BRD)

Baro-VNAV NA when using Aiklin altimeter setting. DME/DME RNP-0.3 NA. Procedure NA when R-4301 is active. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). When local altimeter setting not received, use Aiklin altimeter setting and increase all DA 52 feet and all MDA 60 feet, increase LPV and LNAV/VNAV visibility ¼ mile all Cats, and LNAV Cats C and D visibility ¼ mile. VDP NA with Aiklin altimeter setting.

MISSED APPROACH: Climb to 3000 direct EYUPO and hold.

ASOS 126.775	MINNEAPOLIS CENTER 118.05 239.0	UNICOM 122.7 (CTAF) 0
------------------------	---	---------------------------------



UHAVE		3000		EYUPO	
		050°		*1.4 NM to RW05	
GP 3.00°		2300		*LNAV only	
TCH 46		6.2 NM			
		1.9 NM			
		1.4 NM			
CATEGORY		A	B	C	D
LPV DA		1424-¾		200 (200-¾)	
LNAV/VNAV DA		1777-2		553 (600-2)	
LNAV MDA	1700-1	476 (500-1)		1700-1½	476 (500-1½)
				476 (500-1½)	
CIRCLING	1760-1	528 (600-1)		1760-1½	1860-2
				528 (600-1½)	628 (700-2)

