



LOC I-DVS 111.9	APP CRS 357°	Rwy Ldg TDZE Apt Elev	8501 790 794
---------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 35

GERALD R FORD INTL (G.R.R.)

DME required. DME or RADAR required for procedure entry.	MALSR	MISSED APPROACH: Climb to 1300 then climbing left turn to 3000 on VIO VOR/DME R-353 to WALKS 13.7 DME and hold.
HONSE fix minimums: for inop ALS, increase Cat C and D visibility to RVR 6000. ** RVR 1800 authorized with use of FD or AP or HUD to DA.		

ATIS 118.725	GREAT LAKES APP CON ★ 128.4 257.6	GRAND RAPIDS TOWER ★ 135.65 (CTAF) 0 339.8	GND CON 121.8	CLNC DEL 119.3	UNICOM 122.95
------------------------	---	--	-------------------------	--------------------------	-------------------------



1300	3000	WALKS	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 74). VIO VOR/DME CALDO OM/RADAR JUDD VIO 6.4				One Minute Holding Pattern
*LOC only.	*VIO 3.8	HONSE INT VIO 2.9	2412	177°	357°	5200	
VIO 4.9				357°		3000	
	1.1 NM	0.9 NM	2.9 NM	6.4 NM			
CATEGORY	A	B	C	D			
S-ILS 35**	990/24		200 (200-½)				
S-LOC 35	1480/24	690 (700-½)	1480-1½	690 (700-1½)			
CIRCLING	1480-1	686 (700-1)	1480-2 686 (700-2)	1480-2¼ 686 (700-2¼)			
HONSE MINIMUMS (ADF OR DME REQUIRED)							
S-LOC 35	1200/24	410 (500-½)	1200/40	410 (500-¾)			
CIRCLING	1260-1	466 (500-1)	1340-1½ 546 (600-1½)	1360-2 566 (600-2)			