

APP CRS  
**179°**

Rwy Idg  
TDZE  
Apt Elev

**4855**  
**912**  
**912**

**RNAV (GPS) RWY 18**

ANOKA COUNTY/BLAINE (JANES FLD) (A.N.E.)

RNP APCH - GPS.

When local altimeter setting not received, use Crystal altimeter setting and increase all MDA 40 feet and Circling Cat D visibility ¼ SM.  
VDP NA when using Crystal altimeter setting.

MISSED APPROACH: Climbing left turn to 2600 direct RUNRR and hold.

|                        |                                            |                                       |                          |                          |                                                |                         |
|------------------------|--------------------------------------------|---------------------------------------|--------------------------|--------------------------|------------------------------------------------|-------------------------|
| ATIS<br><b>120.625</b> | MINNEAPOLIS APP CON<br><b>126.5 335.65</b> | ANOKA TOWER★<br><b>132.4 (CTAF) 0</b> | GND CON<br><b>121.85</b> | CLNC DEL<br><b>121.3</b> | CLNC DEL<br><b>121.85</b><br>(When twr closed) | UNICOM<br><b>122.95</b> |
|------------------------|--------------------------------------------|---------------------------------------|--------------------------|--------------------------|------------------------------------------------|-------------------------|

2600

RUNRR

ELEV 912

TDZE 912

179°

81

4855 X 100

5000 X 100

6

9

27

TWR

36

964

HIRL Rwy 9-27

MIRL Rwy 18-36

REIL Rws 9, 18 and 36

1.3 NM to RWY 18

DOZXU

RUNRR

4 NM Holding Pattern

1.3 NM

2.3 NM

6.1 NM

CATEGORY

A

B

C

D

LNVA MDA

1380-1

468 (500-1)

1380-1 3/8

468 (500-1 3/8)

CIRCLING

1400-1

488 (500-1)

1460-1 1/2

548 (600-1 1/2)

1580-2

668 (700-2)

MINNEAPOLIS, MINNESOTA

ANOKA COUNTY/BLAINE (JANES FLD) (A.N.E.)

Orig-G 03NOV22

45°09'N-93°13'W

**RNAV (GPS) RWY 18**