

WAAS CH 73018 W03A	APP CRS 036°	Rwy Ldg 7030 TDZE 1057 Apt Elev 1066
--	------------------------	---

RNAV (GPS) RWY 3
MANHATTAN RGNL (MHK)

RNP APCH - GPS.

T Circling NA northwest of Rwy 3-21. Rwy 3 helicopter visibility reduction below $\frac{3}{4}$ SM NA. Inop table does not apply to LPV all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to $\frac{1}{8}$ SM, increase LNAV Cats A/B visibility to 1 SM and LNAV Cats C/D visibility to $\frac{1}{8}$ SM.

MALSR



MISSED APPROACH: Climb to 3100 direct BIRME and hold.



ASOS
119.075

MARSHALL AAF GCA★
121.25 269.05


MANHATTAN TOWER ★
118.55 (CTAF) **L**

GND CON
121.85

MISSED APCH FIX



ELEV 1066	D	TDZE 1057
-----------	----------	-----------



CATEGORY	A	B	C	D
LPV DA	1 257-½ 200 (200-½)			
RNAV/ VNAV DA	1 441-¾ 384 (400-¾)			
RNAV MDA	1 460-¾ 403 (400-¾)			
CIRCLING	1 540-1 474 (500-1)	1 620-1 554 (600-1)	1 920-2½ 854 (900-2½)	1 920-2¾ 854 (900-2¾)

