

WAAS CH 50231 W05A	APP CRS 047°	Rwy Idg TDZE 429 Apt Elev 441
--	------------------------	---

RNAV (GPS) RWY 5

NORTH CENTRAL STATE (SF'Z)

RNP APCH - GPS.

⚠


Circling Rwy 15, 33 NA at night. For inoperative MALS, increase LPV all Cats visibility to ¾ mile. For inop ALS, increase LPV all Cats visibility to ¾ SM and LNAV/VNAV all Cats visibility to 1 ½ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

MALS

=

MISSED APPROACH:
Climb to 2000 then
climbing left turn to
2500 direct FOSTY
and hold.

AWOS-3PT 120.775	PROVIDENCE APP CON ★ 123.675 244.875	CLNC DEL 124.35	UNICOM 123.075 (CTAF) 0
----------------------------	--	---------------------------	-----------------------------------



WALLU		MIMIC		IDIKE		FOSTY	
2600		2500		2500		2500	
GP 3.00° TCH 52		047°		1.1 NM to RW05		△	
5.9 NM		3.4 NM		1.9 NM		1.1	
CATEGORY	A	B	C	D			
LPV DA	700-¾	271 (300-¾)			NA		
LNAV/ VNAV	835-1	406 (400-1)			NA		
LNAV MDA	820-¾	391 (400-¾)	820-7/8	391 (400-7/8)	NA		
CIRCLING	900-1	459 (500-1)	900-1½	459 (500-1½)	NA		

