

WAAS
CH **40208**
W35A

APP CRS
355°

Rwy Idg **8006**
TDZE **163**
Apt Elev **214**

RNAV (GPS) RWY 35

BOB SIKES (CEW)

RNP APCH.


▼

▲

Baro-VNAV and VDP NA when using Eglin AFB altimeter setting. Rwy 35 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C. When local altimeter setting not received, use Eglin AFB altimeter setting and increase LPV DA to 509, LNAV/VNAV DA to 550, and all MDA 60 feet, increase LNAV Cat C/D visibility ½ SM.

MISSED APPROACH: Climb to 2000 direct WEDOM and hold.

ASOS 119.275	EGLIN APP CON 124.05 284.65	UNICOM 123.075 (CTAF) 0
------------------------	---------------------------------------	-----------------------------------



ELEV 214

TDZE 163

2000

WEDOM

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 61).

4 NM Holding Pattern

*LNAV only.

*1.3 NM to RW35

HEKLU

1600

175°

355°

6000

2000

GP 3.00°
TCH 52

1.3 NM

3 NM

6 NM

CATEGORY	A	B	C	D
LPV DA	450-1	287 (300-1)		
LNAV/VNAV DA	491-1¼	328 (300-1¼)		
LNAV MDA	640-1	477 (500-1)	640-1⅜	477 (500-1⅜)