

MAYNR THREE DEPARTURE (RNAV)

**TOP ALTITUDE:
ASSIGNED BY ATC**



RNAV 1 - DME/DME/IRU or GPS.
From SLIPT to MAXIM: RNAV 1- GP
From SLIPT to CANOA: RNAV 1- G

RADAR required for non-GPS equipped aircraft.
RADAR required.

TAKEOFF MINIMUMS

Rvwy 9L: Standard with minimum climb of 500'/NM to 1300.
Rvwy 9R: Standard with minimum climb of 500'/NM to 1500.
Rvwy 13: Standard with minimum climb of 500'/NM to 1800.
Rvwy 27L: Standard with minimum climb of 500'/NM to 1900.
Rvwy 27R: Standard with minimum climb of 500'/NM to 1700.
Rvwy 31: Standard with minimum climb of 500'/NM to 1400.
Rvwy 37: Standard with minimum climb of 500'/NM to 1400.

NOTE: Jet aircraft only.
NOTE: Accelerate to 250K until leaving 10000, if unable, advise ATC.

MSA TMB 25 NM

291

MIAMI DEP CON	125.5	354.1
ATIS		
124.0		
CLINC DEL		
133.0		
GND CON		
121.7		
MIAMI EXEC TOW		
118.9 (CTAF)		

AUSTI
5000

2020-2021

VR

0003426

LAW

E1180

*1300

SLIPT

0811-

003174

* 1250



2

08

003

1515

,

12

10

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

SE-3, 02 OCT 2025 to 30 OCT 2025

MAYNR THREE DEPARTURE (RNAV)

(MAYNR3.MAYNR) 31OCT24

MIAMI, FLORIDA
MIAMI EXEC (TMB)