

WAAS
CH **70425**
W02A

APP CRS
016°

Rwy Idg **5500**
TDZE **666**
Apt Elev **666**

RNAV (GPS) RWY 2

ROCK HILL/YORK COUNTY/BRYANT FLD (UZA)

▼


▲

Baro-VNAV and VDP NA when using Charlotte/Douglas Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -9°C (16°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Charlotte/Douglas Intl altimeter setting and increase all DA 45 feet and all MDA 60 feet. Increase LNAV/VNAV all Cats visibility ¼ mile and LNAV Cat C/D visibility ¼ mile.

MALSRL

MISSED APPROACH:
Climb to 1600 then climbing left turn to 3000 direct CONEL and hold.

ASOS 120.775	CHARLOTTE APP CON 120.05 307.8	GCO 121.725	UNICOM 123.05 (CTAF) 0
------------------------	--	-----------------------	---



4 NM Holding Pattern		CONEL		1600	3000	CONEL
3000		016°		AZAKA		
GP 3.00° TCH 41		016°		2500		
		2500		*1.2 NM to RW02		
		6 NM		*LNAV only.		
		4.4 NM		RW02		
		1.2 NM				
CATEGORY		A	B	C	D	
LPV DA		866-½		200 (200-½)		
LNAV/VNAV DA		1022-¾		356 (400-¾)		
LNAV MDA		1100-½	434 (500-½)	1100-¾	434 (500-¾)	
CIRCLING		1140-1 474 (500-1)	1160-1 494 (500-1)	1340-2 674 (700-2)	1340-2¼ 674 (700-2¼)	

