

WAAS CH 56327 W27A	APP CRS 276°	Rwy Idg 6579 TDZE 1328 Apt Elev 1328
--	------------------------	---



RNAV (GPS) RWY 27
GAYLORD RGNL (GLR)

RNP APCH - GPS.

- T** Circling Rwy 18, 36 NA at night. Rwy 27 helicopter visibility reduction below $\frac{3}{4}$ SM NA.
A VDP NA when using GOV altimeter setting. When local altimeter setting not received, use GOV altimeter setting: increase LPV DA to 1648 feet; increase all MDAs 80 feet and LNAV visibility Cats C and D $\frac{3}{8}$ SM and Circling visibility Cats C and D $\frac{1}{4}$ SM.

MISSED APPROACH: Climb to 3000 direct WODIV and hold.

ASOS 118.375	MINNEAPOLIS CENTER 134.6 354.05	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------------



CATEGORY	A	B	C	D
LPV DA	1578-1 250 (300-1)			
LNAV MDA	1840-1 512 (600-1)	1840-1 ³ / ₈ 512 (600-1 ³ / ₈)		
CIRCLING	1840-1 512 (600-1)	1940-1 612 (700-1)	2040-2 712 (800-2)	2080-2 ¹ / ₂ 752 (800-2 ¹ / ₂)