

WAAS CH 45533 W28A	APP CRS 282°	Rwy Idg TDZE 941 Apt Elev 941
--	------------------------	---

RNAV (GPS) RWY 28

BROOKS FLD (RMY)

RNP APCH - GPS.

▼


Rwy 28 helicopter visibility reduction below ¾ SM NA. Circling Rwy 10 NA at night.

▲

When local altimeter setting not received, use BTL altimeter setting: increase all MDAs 40 feet and increase LP and LNAV Cat C visibility ½ SM and Circling Cat C visibility ¼ SM. VDP NA with BTL altimeter setting.

MISSED APPROACH: Climb to 1500 then climbing left turn to 3100 direct AWSOF and hold.

AWOS-3 120.025	GREAT LAKES APP CON ★ 119.2 239.25	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



ELEV 941	TDZE 941	1500	3100	AWSOF	VGSI and descent angles not coincident (VGSI Angle 4.00/TCH 37).	4 NM Holding Pattern
CATEGORY	A	B	C	D		
LP MDA	1320-1	379 (400-1)		NA		
LNAV MDA	1320-1	379 (400-1)		NA		
CIRCLING	1440-1	499 (500-1)	1660-2 719 (800-2)	NA		

EC-1, 02 OCT 2025 to 30 OCT 2025

EC-1, 02 OCT 2025 to 30 OCT 2025