



LOC/DME I-SMF 111.1 Chan 48	APP CRS 168°	Rwy Ldg 8598 TDZE 25 Apt Elev 27
---	------------------------	---

ILS or LOC RWY 17R
SACRAMENTO INTL (SMF)

Aircraft not GPS equipped - RADAR required for procedure entry. DME or RADAR required. RNP APCH-GPS. From TENCO.		ALSIF-2 	MISSED APPROACH: Climb to 500 then climbing right turn to 2000 on heading 350° and SAC VORTAC R-329 to GRIME INT/SAC 35.2 DME and hold.		
Simultaneous approach authorized. Circling NA east of Rwy 17R-35L.					
D-ATIS 126.75	NORCAL APP CON 125.4 259.1 (W-NE) 125.25 257.9 (SW) 127.4 317.5 (E-SE)	CAPITOL TOWER 125.7 256.7	GND CON 121.7 256.7	CLNC DEL 121.1 256.7	CPDLC



500 ↑ 2000 hdg 350° SAC R-329		GRIME △	VGS I and ILS glidepath not coincident (VGS I Angle 3.00/TCH 72).	
I-SMF 1.9 IM 0.1 1.2 NM KAYEG I-SMF 3.2 480		JARNU I-SMF 7.3 RADAR 1800 168° 1800	FAPIN I-SMF 9.3 RADAR 1800 GS 3.00° TCH 57	
CATEGORY	A	B	C	D
S-ILS 17R	225/18		200 (200-½)	
S-LOC 17R	480/24	455 (500-½)	480/45	455 (500-¾)
C CIRCLING	480-1	453 (500-1)	480-1½ 453 (500-1½)	580-2 553 (600-2)
KAYEG FIX MINIMUMS (DME REQUIRED)				
S-LOC 17R	400/24	375 (400-½)	400/35	375 (400-¾)
C CIRCLING	440-1 413 (500-1)	480-1 453 (500-1)	480-1½ 453 (500-1½)	580-2 553 (600-2)

SW-2, 02 OCT 2025 to 30 OCT 2025

SW-2, 02 OCT 2025 to 30 OCT 2025