



WAAS CH 90441 W32A	APP CRS 316°	Rwy Idg TDZE Apt Elev	3650 1245 1245
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 32
COUNCIL BLUFFS MUNI (CBF)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP- 0.3 NA.	MISSED APPROACH: Climb to 2000 then climbing right turn to 3900 direct EVHAP and hold.
---	--

AWOS-3 126.575	OMAHA APP CON 124.5 263.0	CLNC DEL 127.675	UNICOM 122.725 (CTAF) ①
--------------------------	-------------------------------------	----------------------------	--



2000	3900	EVHAP	VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 30). 4 NM Holding Pattern			
* LNAV only	CAVPI 1.7 NM to RW32	FEHEV	EVHAP	136°	3900	GP 3.00° TCH 40
* 0.9 NM to RW32	1820*	2900	316°	316°		
0.9	0.8	3.4 NM	7 NM			
CATEGORY	A	B	C	D		
LPV DA		1445-¾	200 (200-¾)			
LNAV/VNAV DA		1495-¾	250 (300-¾)			
LNAV MDA		1620-1	375 (400-1)			
☑ CIRCLING	1780-1	535 (600-1)	1780-1½ 535 (600-1½)	1880-2 635 (700-2)		