

WAAS CH 87030 W 13A	APP CRS 135°	Rwy Idg TDZE 1203 Apt Elev 1204
---	------------------------	---

RNAV (GPS) RWY 13




ARTHUR N NEU (CIN)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Audubon altimeter setting. When local altimeter setting not received, use Audubon altimeter setting; increase LPV DA to 1515 feet; increase LNAV/VNAV DA to 1669 feet and all visibilities ¼ SM; increase all MDAs 80 feet and visibility Cat C ¼ SM.

MISSED APPROACH: Climb to 3000 direct COHGI and hold.

AWOS-3 118.025	MINNEAPOLIS CENTER 134.0 288.3	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



CATEGORY	A	B	C	D
LPV DA	1453-1	250 (300-1)		NA
LNAV/VNAV DA	1607-1⅜	404 (500-1⅜)		NA
LNAV MDA	1620-1	417 (500-1)	1620-1⅛ 417 (500-1⅛)	NA
CIRCLING	1740-1	536 (600-1)	1980-2¼ 776 (800-2¼)	NA