

ILS or LOC RWY 12
SOUTHWEST MINNESOTA RGNL MARSHALL/RYAN FLD (MML)

NA When local altimeter setting not received, use Tracy Muni altimeter setting and increase ILS DA to 1441 feet and all MDA 60 feet, S-LOC Cat C/D visibility $\frac{1}{8}$ SM and Circling visibility Cat C/D $\frac{1}{4}$ SM. Inop table does not apply. For inop ALS increase S-LOC 12 all Cats visibility to 1 SM. Inop table does not apply when using Tracy Muni altimeter setting. For inop ALS when using Tracy Muni altimeter setting, increase S-LOC 12 Cat A/B visibility to 1 SM.



MISSED APPROACH: Climb to 2000 then climbing left turn to 3000 direct GARNO LOM/ MML 4.9 DME and hold.

2132

305°

170°

350°

125°

305°

3000

306° (4.9)

1299±

1274±

1514

LOM/IAF
GARNO
253 GB

MML 4.9

1969

LOCALIZER
I-GBY
109.7

REDWOOD FALLS
113.3 RWF
Chan 80

3000
267°
(33.7)

MARSHALL
111.0 MML
Chan 47

1999

1913

3500

331°
(63.3)

SIOUX FALLS
115.0 FSD
Chan 97

MSA GB 25 NM

090°

360°

3400

3800

ALTERNATE
MISSED APCH FIX

MARSHALL
MML
111.0
Chan 47

130°

310°

R-130

ELEV 1183

TDZE 1183

125° 4.1 NM
from FAF

FAF to MAP 4.1 NM					
Knots	60	90	120	150	180
Min:Sec	4:06	2:44	2:03	1:38	1:22