

WAAS CH 82106 W12A	APP CRS 125°	Rwy Idg 7221 TDZE 1183 Apt Elev 1183
--	------------------------	---

RNAV (GPS) RWY 12

SOUTHWEST MINNESOTA RGNL MARSHALL/RYAN FLD (MML)

RNP APCH-GPS

T Baro-VNAV and VDP NA when using Tracy Muni altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 36°C. When local altimeter setting not received, use Tracy Muni altimeter setting and increase LPV DA to 1441 feet; LNAV/VNAV DA to 1548 and all Cats visibilities $\frac{1}{2}$ SM; increase all MDA 60 feet, LNAV visibility Cat C/D $\frac{1}{8}$ SM and Circling visibility Cat C/D $\frac{1}{4}$ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to $\frac{1}{2}$ SM, and LNAV Cat C/D visibility to 1 SM. For inop ALS when using Tracy Muni altimeter setting, increase LNAV/VNAV all Cats visibility to 1 SM.

MALS



MISSED APPROACH:
Climb to 3000 direct
BOPMY and hold.

AWOS-3PT 120.150	MINNEAPOLIS CENTER 127.1 290.2	GCO 121.725	UNICOM 122.8 (CTAF) 0
----------------------------	--	-----------------------	---------------------------------

