

VOR/DME MML

111.0

Chan 47

APP CRS

130°

Rwy Idg

7221

TDZE

1183

Apt Elev

1183

SOUTHWEST MINNESOTA RGNL MARSHALL/RYAN FLD (MML)

VOR RWY 12

NA

For inop ALS, increase S-12 Cat C/D visibilities to 1½ SM, CEGUL fix minimums: S-12 Cat C/D visibility to 1 SM. For inop ALS when using Tracy altimeter setting increase S-12 Cat C/D visibilities to 1¾ SM. When local altimeter setting not received, use Tracy Muni altimeter setting and increase all MDAs 60 feet, S-12 Cat C/D visibility ½; Circling Cat C/D visibility ¾ SM; CEGUL fix minimums: increase Circling C/D visibility ¼ SM. VDP NA when using Tracy Muni altimeter setting.

MALSR

MISSED APPROACH: Climb to 2000, then climbing left turn to 2800 direct MML VOR/DME and hold.

AWOS-3PT 120.150	MINNEAPOLIS CENTER 127.1 290.2	GCO 121.725	UNICOM 122.8 (CTAF)
---------------------	-----------------------------------	----------------	------------------------

ELEV 1183		TDZE 1183	
Remain within 10 NM		2000 2800 MML	
310° 2800 130° 1760		130° to VOR/DME	
CEGUL MML 3			
MML 1.9			
1.1 NM 1.1 NM			
CATEGORY	A	B	C D
S-12	1760-½ 577 (600-½)	1760-1¼ 577 (600-1¼)	
CIRCLING	1760-1 577 (600-1)	1820-1¾ 637 (700-1¾)	1840-2 657 (700-2)
CEGUL FIX MINIMUMS			
S-12	1560-½ 377 (400-½)	1560-¾ 377 (400-¾)	
CIRCLING	1640-1 457 (500-1)	1820-1¾ 637 (700-1¾)	1840-2 657 (700-2)
MARSHALL, MINNESOTA		SOUTHWEST MINNESOTA RGNL MARSHALL/RYAN FLD (MML)	
Amdt 8C 15JUL21		44°27'N-95°49'W	

VOR RWY 12