

WAAS
CH **77531**
W03A

APP CRS
033°

Rwy Idg **4748**
TDZE **1177**
Apt Elev **1182**

RNAV (GPS) RWY 3

UNIVERSITY OF OKLAHOMA WESTHEIMER (OUN)

▼

Baro-VNAV NA when using Will Rogers World altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F).

⚠


DME/DME RNP-0.3 NA. When local altimeter setting not received, use OKC Will Rogers Intl altimeter setting and increase LPV DA to 1501 feet, LNAV/VNAV DA to 1544 feet; increase all MDA 60 feet, increase LPV visibility to 7⁄8 mile all Cats, increase LNAV/VNAV visibility to 1 mile all Cats, and increase LNAV Cat C/D visibility to 1 1⁄8 mile. For inop MALS, increase LPV all Cats visibility to 1 mile, LNAV/VNAV Cat D visibility to 1 1⁄8 mile, LNAV Cat C/D visibility to 1 1⁄8 mile. For inop MALS when using OKC Will Rogers Intl altimeter setting, increase LPV all Cats visibility to 1 1⁄8 mile, LNAV/VNAV Cat D visibility to 1 1⁄4 mile, LNAV Cat D visibility to 1 1⁄8 mile. Circling NA southeast of Rwy 3 and 21.

MALS

MISSED APPROACH:

Climb to 1700 then climbing right turn to 3100 direct WETIX and hold.

AWOS-3PT 119.55	OKE CITY APP CON 120.45 288.325	WESTHEIMER TOWER* 118.0 (CTAF) 0	GND CON 121.6	UNICOM 122.95
---------------------------	---	---	-------------------------	-------------------------



4 NM Holding Pattern

AXETE

3000 ← 213°

033° →

SOPNE

2800

GP 3.00° TCH 40

4 NM

2.1 NM

1.8 NM

1.6 NM

1700

3100

WETIX

*LNAV only

USUYO 1.6 NM to RWY03

RWY03

*1720

2300

EJISO 2300

CATEGORY	A	B	C	D
LPV DA		1460-3⁄4	283 (300-3⁄4)	
LNAV/VNAV DA		1503-7⁄8	326 (400-7⁄8)	
LNAV MDA	1580-3⁄4	403 (400-3⁄4)	1580-1	403 (400-1)
CIRCLING	1660-1	478 (500-1)	1940-2 1⁄4 758 (800-2 1⁄4)	1940-2 1⁄2 758 (800-2 1⁄2)

ELEV 1182

TDZE 1177