

WAAS CH 97628 W06A	APP CRS 058°	Rwy Idg TDZE Apt Elev	5004 733 733
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 6

DAVIDSON COUNTY EXEC (E.XX)



⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). When local altimeter setting not received, use Salisbury altimeter setting and increase all DA 37 feet and all MDA 40, increase LPV, LNAV/VNAV all Cats and LNAV Cat C visibility ½ mile. DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Salisbury altimeter setting.

MALSR

MISSED APPROACH:
Climb to 3000 direct
HACNI and hold.

AWOS-3 119.825	GREENSBORO APP CON 126.6 327.075	GCO 135.075	UNICOM 122.8 (CTAF) 0
--------------------------	--	-----------------------	---------------------------------



4 NM Holding Pattern WOKIR				3000	HACNI
GP 3.00° TCH 40					
VGSi and RNAV glidepath not coincident (VGSi Angle 4.00/TCH 28).					
3000 ← 238° → 058° → 2400					
2400 ← 058° → 1600					
6.8 NM		2.5 NM		1.8 NM	0.8 NM
CATEGORY	A	B	C	D	
LPV DA	983-7/8	250 (300-7/8)		NA	
LNAV/VNAV DA	1020-1	287 (300-1)		NA	
LNAV MDA	1120-1	387 (400-1)	1120-1 1/8 387 (400-1 1/8)	NA	
CIRCLING	1220-1 487 (500-1)	1240-1 507 (600-1)	1340-1 3/4 607 (700-1 3/4)	NA	