

WAAS CH 81836 W05A	APP CRS 054°	Rwy Idg TDZE 255 Apt Elev 270
--	------------------------	---

RNAV (GPS) RWY 5

COLUMBIA/MARION COUNTY (ØRØ)

RNP APCH - GPS.


▼

NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.
When local altimeter setting not received, use Hattiesburgh/Laurel Rgnl altimeter setting and increase all DA 66 feet and all MDA 80 feet; increase LPV all Cats visibility ½ mile and LNAV/VNAV all Cats and Circling Cat C visibilities ¼ mile, increase Circling Cat D visibility ½ mile, increase LNAV Cat C and D visibility ¾ mile. VDP and Baro-VNAV NA when using Hattiesburgh/Laurel Rgnl altimeter setting. Rwy 5 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 2400 direct
NERAE and hold.

AWOS-3PT 120.675	HOUSTON CENTER 126.8 327.8	UNICOM 122.8 (CTAF)Ø
----------------------------	--------------------------------------	--------------------------------



ELEV 270		TDZE 255	
4 NM Holding Pattern		2400 NERAE	
2400 ← 234° 054° →		*1500 ZOSOG	
GP 3.00° TCH 40		*1.5 NM to RW05 RW05	
6.1 NM		1.8 NM	
CATEGORY		A	
LPV DA		505-7½ 250 (300-7½)	
LNAV/VNAV DA		743-1½ 488 (500-1½)	
LNAV MDA		760-1 505 (500-1) 760-1¾ 505 (500-1½)	
CIRCLING		760-1 490 (500-1) 820-1 550 (600-1) 920-1¾ 650 (700-1¾) 1000-2¼ 730 (800-2¼)	
		REIL Rwy 5 and 23Ø MIRL Rwy 5-23Ø	

SC-4, 02 OCT 2025 to 30 OCT 2025

SC-4, 02 OCT 2025 to 30 OCT 2025