

WAAS
CH **99719**
W16A

APP CRS
164°

Rwy Idg
TDZE **99**
Apt Elev **100**

RNAV (GPS) RWY 16

YOLO COUNTY (DWA)

RNP APCH.

When local altimeter setting not received, use Travis AFB altimeter setting and increase all DA 50 feet and all MDA 60 feet, and increase LNAV/VNAV all Cats and LNAV Cat C and D visibility ¼ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 43°C (109°F). Baro-VNAV NA when using Travis AFB altimeter setting.

MISSED APPROACH: Climb to 3600 direct PROAP and hold, continue climb-in-hold to 3600.

AWOS-3P
125.775

TRAVIS APP CON
126.6 281.45

UNICOM
123.0 (CTAF)

Procedure NA for arrivals at ILA VORTAC airway radials 057 CW 210.

Procedure NA for arrivals at COUPS on V6 southbound.

MSA RW 16 25 NM

4300

3038, 2430, 3057, 2368

(IAF) WILLIAMS ILA 3000 NoPT 139° (18.8)

(IAF) ELEGY 3000 NoPT 095° (11.3)

(IF/IAF) GHEER 2000 164° (6.2)

(FAF) YOLOH 220± 1.7 NM to RW16

GAAAS 192± 4 NM 164° 344°

PROAP 3000 to GHEER 325° (29.8)

A-682, COUPS

ELEV 100 TDZE 99

164° to RW16

91

001 X 0009

34

3600	PROAP	YLOH	GHEER	4 NM Holding Pattern
*LNAV only	GAAAS 1.7 NM to RW16	2000	3000	GP 3.00° TCH 40
RW16 1.7 NM		4.2 NM	6.2 NM	
CATEGORY	A	B	C	D
LPV DA	360-1 261 (300-1)			
LNAV/VNAV DA	402-1 303 (400-1)			
LNAV MDA	480-1 381 (400-1)		480-1½ 381 (400-1½)	

MIRL Rwy 16-34