

WAAS CH 63009 W24A	APP CRS 240°	Rwy Idg 5501 TDZE 523 Apt Elev 526
--	------------------------	---




RNAV (GPS) RWY 24
HENDERSON/OXFORD (HNZ)

RNP APCH - GPS.

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Baro-VNAV and VDP NA when using Roxboro altimeter setting. Rwy 24 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Roxboro altimeter setting and increase LPV DA to 837 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 877 feet and all visibilities ½ SM; increase all MDAs 80 feet and LNAV visibility C/D ¾ SM, and Circling visibility C/D ¼ ½ SM.

MISSED APPROACH:
Climb to 3000 direct
KOVPE and hold.

AWOS-3 118.625	RALEIGH APP CON 132.35 256.9	UNICOM 122.8 (CTAF) 0
--------------------------	--	--



CATEGORY	A	B	C	D
LPV DA	773- ³ / ₄		250 (300- ³ / ₄)	
LNAV/ VNAV DA	813- ⁷ / ₈		290 (300- ⁷ / ₈)	
LNAV MDA	900-1		377 (400-1)	
C CIRCLING	960-1 434 (500-1)	980-1 454 (500-1)	1100-1 ¹ / ₂ 574 (600-1 ¹ / ₂)	1280-2 ¹ / ₂ 754 (800-2 ¹ / ₂)

