

WAAS

CH **61009**

W27A

APP CRS

273°

Rwy Ldg

4000

TDZE

1073

Apt Elev

1082

RNAV (GPS) RWY 27

MADISON COUNTY (UYF)

RNP APCH - GPS

▼

▲

Rwy 27 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C.

AWOS-3PT

120.85

COLUMBUS APP CON

134.0 279.6

UNICOM

123.0 (CTAF) 0

ELEV	1082	TDZE	1073
------	------	------	------

3000

FENLU

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 31).

4 NM Holding Pattern

*LNAV only.

JADMU 2.1 NM to RWY 27

FOFWI 2700

AKPUC

093° → 8000

← 273° 3000

GP 3.00° TCH 40

1.4

0.7

2.9 NM

6.2 NM

CATEGORY	A	B	C	D
LPV DA	1400-1¼ 327 (400-1¼)			
LNAV/VNAV DA	1449-1½ 376 (400-1½)			
LNAV MDA	1540-1	467 (500-1)	1540-1¾ 467 (500-1¾)	1540-1½ 467 (500-1½)
CIRCLING	1600-1 518 (600-1)	1640-1 558 (600-1)	1640-1½ 558 (600-1½)	1840-2½ 758 (800-2½)

LONDON, OHIO

Orig-B 11AUG22

39°56'N-83°28'W

RNAV (GPS) RWY 27

MADISON COUNTY (UYF)