

WAAS CH 87108 W18A	APP CRS 181°	Rwy Ldg TDZE Apt Elev	5001 684 685
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 18

STARKE COUNTY (OXI)

RNP APCH - GPS.


▼

▲

Baro-VNAV and VDP NA when using SBN altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Circling NA to Rwys 9 and 27.
When local altimeter setting not received, use SBN altimeter setting: increase LPV DA to 1010 feet; increase LNAV/VNAV DA to 1136 feet and all visibilities ¾ SM; increase all MDAs 80 feet and LNAV visibility Cat C and D ¾ SM, and Circling visibility Cat C and D ¼ SM.

MISSED APPROACH:
Climb to 1200 then climbing left turn to 3000 direct SELOE and hold.

AWOS-3 135.775	SOUTH BEND APP CON ★ 132.05 257.8	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------



ELEV 685

TDZE 684

4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 27).

1200 3000 SELOE

NUVIC

YAGPU

WAVGO 2.5 NM to RWY 18

1.1 NM to RWY 18

RWY 18

GP 3.00° TCH 40

5.9 NM 2.5 NM 1.4 NM 1.1 NM

CATEGORY	A	B	C	D
LPV DA		934-1	250 (300-1)	
LNAV/VNAV DA		1060-1	376 (400-1)	
LNAV MDA		1060-1	376 (400-1)	
CIRCLING	1120-1 435 (500-1)	1140-1 455 (500-1)	1380-2 695 (700-2)	1380-2 ¼ 695 (700-2 ¼)

MIRL Rwy 18-36

REIL Rwys 18 and 36 0